

BFM® Fittings

Improve your process sanitation and reduce connector changeout times by switching to BFM® Fittings.

Easy as Snap-In, Snap-Out

Snap-in, snap-out convenience in a variety of diameters, lengths, compounds and custom configurations. If you're tired of maintenance issues and plant downtime caused by frequent connector replacement, BFM® Fittings are your solution.



VARIETY OF SIZES AND COMPOUNDS

BFM® Fittings are available in a variety of diameters, lengths and connector compounds. The system is composed of 304 or 316 SS spigots and flexible connectors with matching molded end fittings that interlock with and disconnect from the spigots without the need of tools.

SPIGOT DIAMETERS:

- 4 inch / 100 mm
- 5 inch / 125 mm
- 6 inch / 150 mm
- Up to 26 inch / 650 mm

STANDARD LENGTHS:

- 4 inches / 100 mm
- 6 inches / 150 mm
- 8 inches / 200 mm

Additional lengths in 50mm increments and tapered connectors are available by special order.

HIGHLIGHTS



- NO HOSE CLAMPS means fast snap-in/ snap-out convenience.
- DUST-TIGHT CONNECTIONS means greatly improved dust control.
- PERFECT FIT means no leaks and better plant sanitation.
- REDUCED DUST **AND LEAKAGE** means safer plant operation.
- QUICK **CHANGE-OUT** means reduced plant downtime.
- VACUUM PROOF and overpressure proof and explosion resistant.











NO TOOLS OR BAND CLAMPS REQUIRED

BFM® Fitting system requires a steel spigot to be mounted to each equipment port, which then allows the BFM connector to be snapped in and out without tools or band clamps. BFM® Fitting spigots are available in 304L stainless steel and 316L stainless steel.

A variety of spigot base forms are available to permit welding or bolting of the spigot to the equipment. The weldable spigot form can be adapted to nearly any mounting type.

- Weldable tubing extension
- QuickConnect[™] modular flanges
- Tri-Clover™ sanitary clamps
- Standard flanges
- Compression couplings



Siftex Equipment Co., Inc. 52D Connecticut Avenue South Windsor, CT 06074 USA

Toll Free 800.274.3839 Local 860.289.8779 860.289.8744 Fax

customerservice@siftex.com





BFM° FITTING CONNECTOR OFFERINGS:



Blanking Sock

Bulk Bag Loader

Teflex Opaque