

CUSTOMER

Certificate of Compliance

Clear-Flex SDX

| DESCRIPTION | YES | NO | NA |
|---------------------------------------|-----|----|----|
| ISO 9001:2015 QMS | | ✓ | |
| FDA 21 CFR 177.2800 (TEXTILES) | | | ✓ |
| FDA 21 CFR 177.2600 (RUBBER ARTICLES) | | | ✓ |
| FDA 21 CFR 177.1680 (POLYURETHANE) | ✓ | | |
| CALIFORNIA PROPOSITION 65 | | | ✓ |
| REACH | ✓ | | |
| RoHS | | | ✓ |
| EC1935/2004 | | | ✓ |
| EC2023/2006 | ✓ | | |
| EC10/2011 | ✓ | | |
| EU DIRECTIVE 2014/34 (ATEX) | ✓ | | |
| PHTHALATE / BPA FREE | ✓ | | |
| TSE / BSE / ADI FREE | ✓ | | |
| LATEX RUBBER FREE | | ✓ | |
| CONTAINS 3TG MINERALS | | ✓ | |

| | |
|----------------------|-------------------------------|
| Clear-Flex SDX | CFT-SDX 020 040 060 |
| Abrasion-Resistance | Outstanding |
| Temperature Range | -40-223 F / -40-106 C |
| Durometer (Shore A) | 90 |
| Tear Strength, Die C | 460.0 LBS/IN2 |
| Ultimate Elongation | 590% |
| Tensile Strength | 3060 PSI |
| Taber Abrasion | 39 MG |
| Surface Resistance | 1.4 X 10 ⁶ OHM/SQ |
| Static Decay | 0.50 SECONDS |
| Specific Gravity | 1.12 |
| Wall Thickness | .035" .020" .040" .060" |

I do hereby certify that the products and/or services supplied on the above referenced invoice number are of the quality specified and conform to all requirements of the purchase order, including quality control, design and material specifications, drawings, packaging, marking and physical identification requirements as well as regulatory requirements as indicated above.

Steven E. Weil

President